

PREMIUMPLUS REGULATOR

SECONDARY



DEDICATED TO
DRAFT QUALITY

SECONDARY

FEATURES

- High performance
- Accurate pressure control
- Designed to be non-serviceable
- Integrated pressure relief valve (option)
- Stainless steel valve seat
- Zn/Ni plated brass housings
- SK approved
- Individually numbered for traceability
- Adjust screw protected by tamper evident cap
- Tamper evident cap breaks to access adjust screw
- Allen key adjustment (key included)
- Tamper evident ring between housings

SPECIFICATION

- Material:
 - body: Brass Zn/Ni plated
 - valve seat: Stainless steel
 - connections: Brass Zn/Ni plated
 - brackets: Stainless steel
- Connection: with or without shut-off valve
 - outside thread: 1/2" – 5/8" – 3/4" BSP
 - inside thread: 1/4" NPT
 - push-in: JG 3/8" - JG 5/16"
 - others: on request
- Inlet pressure: 3-7 bar

SPECIFICATION

- Working pressure: 0.5-7 bar
- Low pressure gauge: optional
- Pressure relief valve: settings are customised - additional PRV is an option
- Capacity: 50 l/min maximum
- Weight: variable from approx 0.7 kg
- Dimensions mm: variable from approx 120 x 85 x 90
- Media: CO₂, N₂ and mixed gases

BENEFITS

- Stable CO₂ pressure
- Inlet filter (100 microns)
- Venting function – easy adjustment
- Maintenance free
- Modern production facilities
- Single product identity (number)
- Comply with EU Directive
- Manufacturing in accordance with ISO 9001 quality control system

