

PREMIUMPLUS REGULATOR

# SECONDARY



DEDICATED TO  
DRAFT QUALITY

# SECONDARY

## FEATURES

- High performance
- Accurate pressure control
- Designed to be non-serviceable
- Integrated pressure relief valve (option)
- Stainless steel valve seat
- Zn/Ni plated brass housings
- SK approved
- Individually numbered for traceability
- Adjust screw protected by tamper evident cap
- Tamper evident cap breaks to access adjust screw
- Allen key adjustment (key included)
- Tamper evident ring between housings

## SPECIFICATION

- Material:
  - body: Brass Zn/Ni plated
  - valve seat: Stainless steel
  - connections: Brass Zn/Ni plated
  - brackets: Stainless steel
- Connection: with or without shut-off valve
  - outside thread: 1/2" – 5/8" – 3/4" BSP
  - inside thread: 1/4" NPT
  - push-in: JG 3/8" - JG 5/16"
  - others: on request
- Inlet pressure: 3-7 bar

## SPECIFICATION

- Working pressure: from 0,5bar up to 90% of the nominal pressure indicated on the low-pressure gauge
- Low pressure gauge: optional
- Pressure relief valve: settings are customised - additional PRV is an option
- Capacity: 50 l/min maximum
- Weight: variable from approx 0.7 kg
- Dimensions mm: variable from approx 120 x 85 x 90
- Media: CO<sub>2</sub>, N<sub>2</sub> and mixed gases

## BENEFITS

- Stable CO<sub>2</sub> pressure
- Inlet filter (100 microns)
- Venting function – easy adjustment
- Maintenance free
- Modern production facilities
- Single product identity (number)
- Comply with EU Directive 2014/68/EU
- Manufacturing in accordance with ISO 9001 quality control system

