

QuickFit™

CO₂ REGULATOR



DEDICATED TO
DRAFT QUALITY

CO₂ REGULATOR

FEATURES

- High performance
- Accurate pressure control
- Designed to be non-serviceable
- Protective cover for pressure gauge
- Integrated pressure relief valve
- Stainless steel valve seat
- Red/green pressure indicator for replace of CO₂ cylinder
- Easy and safe handling by replacement of CO₂ cylinder
- Individually numbered for traceability
- Integrated pressure adjustment handle with lock
- Tamper evident seal on pressure adjustment handle - optional
- Customer branding - optional

SPECIFICATION

- Material:
 - body: Brass
 - valve seat: Stainless steel
 - connections: Brass Zn/Ni plated
 - cover: ABS
- Inlet connection: Micro Matic Std. for QuickFit™ (MM1)
- Outlet connection: with or without shot-off valve
 - outside thread: 1/2" - 5/8" - 3/4" BSP
 - inside thread: 1/4" NPT
 - push-in: JG 3/8" - JG 5/16"
 - others: on request
- Inlet pressure: 60 bar CO₂
- Working pressure: 0.5 - 7 bar
- High pressure gauge: Red/green pressure indicator
- Low pressure gauge: Ø40 mm pressure gauge
- Pressure relief device: According to working pressure
- Capacity: 100 L/min max. (continuous)
- Weight: Variable from approx. 0.8 kg
- Dimensions: Variable from approx. 130 x 120 x 95 mm
- Media: Carbon Dioxide / CO₂

BENEFITS

- High capacity CO₂ flow 100 L/min continuous
- Stable CO₂ pressure from full to empty cylinder
- Double inlet filter (100 microns / 100 microns)
- Venting function – easy adjustment
- Maintenance free
- Ergonomic design
- Modern production facilities
- Single product identity
- Comply with EU Directive 2014/68/EU
- Manufacturing in accordance with ISO 9001 quality control system

DIMENSIONS

