

PREMIUMPLUS20 REGULATOR

PRIMARY



DEDICATED TO
DRAFT QUALITY

PREMIUM PLUS 20 PRIMARY

FEATURES

- High performing gas regulator for high gas throughput
- Accurate pressure control system
- Integrated pressure safety relief valve for primary
- Stainless steel cartridge piston
- High precision machined housing
- Each product one serial number for traceability
- Pressure adjusting knob for pressure setting

BENEFITS

- High capacity CO2 flow of 20 L/min continuous
- Supplies 2 taps at a dispense flow rate of 3l/min
- Stable CO2 pressure from full to empty cylinder
- Easy replaceable inlet filter with 100my pore size
- Venting function to release gas for lower setting
- Maintenance free end designed for long life
- Modern production high quality production process
- Comply with Pressure Directive 2014/68/EU
- Manufacturing in accordance with ISO 9001 quality control system

SPECIFICATION

- Material:
 - Regulator body: Brass body with CuNi coating
 - Inlet connection: Stainless steel
- Inlet connections:
 - CO2: W 21.8 x 1/14 or bottle connector for 425g bottle with ACME thread
- Outlet connection: Push-in fitting
 - push-in fitting: Tube size 3/8" or 5/16"
- Inlet pressure: nominal 60 bar (CO2)
- Working pressure: from 0,5bar up to 90% of the nominal pressure indicated on the low-pres- sure gauge
- Low pressure gauge: Standard 0-6bar / 0-10bar
- Pressure relief valve: settings can be customized
Standard 4bar or 7bar
- Capacity: Flow 20 l/min constant gas flow
- Weight: variable from approx. 0.55 kg
- Dimensions mm: variable from approx. 110 x 110 x 70
- Media: CO2 (food grade gas quality only)



PREMIUM PLUS 20 PRIMARY

REGULATOR OPTIONS:

Bottle connection W21.8



Bottle wrench mounted to the regulator nut



Household connection

